

The new Tidel *is2000* represents the latest edition of our high-value, feature-rich ATMs designed exclusively for off premise use.

The *is2000* sets a new standard of versatility, and its host of smart innovations reduce maintenance time and expense.



Each *is2000* features a built-in ATM signage panel. Use your own graphics, or the standard ATM graphics provided.

Sign

- > ATM graphics panel [standard]
- > lighting kit [optional]

CPU

- > mother board card cage assembly [standard]
- > separate cards for CPU, input/output module, electronic journal [standard]

Memory

- > 1 MB [standard]
- > 2 MB with color display [optional]
- > 4 MB [optional] (to support larger graphics files)



Cabinet

- > single-cassette, UL 291 certified [standard]
- > single-cassette, UL 291 business hours listed [optional]
- > long-door, multiple-cassette, UL 291 business hours listed [optional]
- > long-door, multiple-cassette, UL 291 level 1 listed [optional]





Electronic components (modems, memory, disk drives, etc.) can be easily serviced or upgraded without requiring access to the vault, improving serviceability and security.

Modem

- > 2400 bps socketed modem [standard]
- > 33.6k bps [optional]



Display

- > monochrome [standard]
- > 256-color [optional]

Security features

- > combination lock [standard]
- > electronic/low security and electronic/high security (managed) locks [optional]
- > proprietary electronic protection of dispenser [standard]

Graphics compatible (downloaded via modem or floppy disk—a Tidel exclusive)

ATM Information Management System (AIMS) compatible

- > remote ATM management
- > state-of-health inquiries
- > inventory checks
- > system performance checks
- > just-in-time ATM support
- > database management
- > low-cost dial-up technology
- > point-and-click interface
- > multi-modem support



Printer

- > thermal graphics printer [standard]
- > mechanical receipt presenter [standard]
- > optical "low paper" sensor [standard]

The printer is easily accessible for service and loading. An optical "low paper" sensor reads the paper core and does not require any special installation or threading, which means fewer misfeeds. A mechanical receipt presenter is standard.



Easy load cassettes (no jigs required). Rejected notes are automatically returned to a separate holding compartment in the cassette. It's also adjustable for multiple currency types and offers separate cassette locking mechanisms for added safety.

Cassette(s)

- > one non-expandable, non-locking cassette [standard]
- > two, three or four cassettes (with long-door cabinet option) [optional]
- > locking cassette(s) [optional]

Customers can start with the cost-effective base model and expand it as needed with additional cassettes, a color monitor, greater memory, faster connectivity and more.

The standard features of the is2000 include:

Cabinet

> single-cassette, UL 291 certified

CPU

> mother board card cage assembly
> separate cards for CPU, input/output module, electronic journal

Display

> monochrome standard

Memory

> 1 MB standard

Cassette(s)

> one non-expandable, non-locking cassette standard

Printer

> thermal graphics printer standard

Surge Protection

> multiple stage surge protector

Modem

> 2400 bps socketed modem standard

Security features

> combination lock standard
> proprietary electronic protection of dispenser standard

Graphics compatible (downloaded via modem or floppy disk – a Tidel exclusive)

ATM Information Management System (AIMS) compatible

> remote ATM management
> state-of-health inquiries
> inventory checks
> system performance checks
> just-in-time ATM support
> database management
> low-cost dial-up technology
> point-and-click interface
> multi-modem support



• Specifications

Weight: 280 Lbs.
Power Requirements: 100-250v AC 50/60Hz, 2.6 AMP.

Power Connections:

Unit recommended to be connected to a dedicated power circuit consisting of "Line", "Neutral" and "Ground" leads connected directly to the power distribution panel.

Phone Line Requirements:

Unit must be connected to a dedicated "tone" or "pulse" telephone that is terminated with a standard wall jack (RS-11C). To insure expected connectivity, unit should not share this line with any other equipment.

Like all Tidel cash and cash value product dispensers, the is2000 ATM comes with our industry-leading one-year warranty on both parts and labor. And Tidel supports our customers with 24-hour, seven-day customer service backed by a network of local dealers and nationwide distributors.